



AUMSHIVAY ENGINEERING PRIVATE LIMITED

Rotary Barrel Pump



Rotary Barrel Pump is manufactured using excellent quality aluminum & zinc plated steel tube. The Offered Rotary Pump is superior to any other with features such as Dual Directional Operation which allows the pump to both empty, as well as refill containers.

ROTARY BARREL PUMP				
PRODUCT	Barrel Pump (Rotary)			
PUMP BODY	Cast Iron/ Mild Steel			
FLOW RATE	20-50 Ltr per min appox.			
SUTABLE FOR	Fits 15 gallons (50 Ltr) to 55 gallons (210 Ltr) barrels			
WETTED COMPONENT	Steel, Cast Iron, NBR/ Viton			
WEIGHING	Extremely Heavy Duty (6.6 Kgs or 14.5 lbs).			
RECOMMENDED USE	For dispensing Diesel, Kerosene, Heating Oils , Motor Oils, Lubricating Oils (upto SAE 90), and other non-corrosive media.			
CONTENTS	Chamber, Handle, Handle Grip, Bend Pipe, Barrel Nut. Comes complete with suction tube, 2" cast iron bung nut & discharge spout.			
DO NOT USE	With water based media, Antifreeze, Solvents, Acids, and Gasoline etc.			

Operation: Pumps in either direction by a few reverse turns of the handle Pump inlet threaded 1° designed for volume discharge of low to medium viscosity media

Dual Directional

CAT. No.	PUMP INLET	SEALS	DISCHARGE SPOUT	SUCTION TUBE
AEPL-20T/SPL	3/4"	NBR	Steel	Telescopic
AEPL-25T/SPL	1"	NBR	Steel	Telescopic
AEPL-25/3R/SPL	1"	NBR	Steel	3pc. Rigid
AEPL-25V/3R/SPL	1"	VITON	Steel	3pc. Rigid
AEPL-25/3R/PRO	1"	NBR	With 1.8m hose & metal nozzle	3pc. Rigid
AEPL-25/3R/PRO	1"	NBR	With 1.8m hose & metal nozzle	Telescopic



PAGE. 1



AUMSHIVAY ENGINEERING PRIVATE LIMITED

B-21, Bhan Nagar, Queens Road, Jaipur-302021
 Website: www.aumshivay.com, www.omengineering.in

 E-mail:admin@aumshivay.com



Robber boot keeps rain water and contaminants away.



Pump with 1" inlet, complete with 1.8m hose and metal nozzle.



use with high viscosity media.



